

STRAIGHT REBAR SPECIFICATIONS

GRADES	ASTM STANDARDS			
	A615-40	A615-60	A615-80	Future Grade: 100
		A706-60	A706-80	
		A615-60/A706 GR 60	A615-80/A706 GR 80	
	CSA G30.18 STANDARDS			
		400R	500R	Future Grade: 600
		400W	500W	

SIZES	US IMPERIAL BAR SIZES										
	#3	#4	#5	#6	#7	#8	#9	#10	#11	#14	#18
	CANADIAN METRIC BAR SIZES										
	10M	15M	20M	25M	30M	35M	45M	55M			

STANDARD LENGTHS

Straight bar bundles are offered in standard lengths of 20', 30', 40', and 60', as well as metric lengths of 6M, 9M, 12M, 15M, 18M. Custom-cut lengths are available with minimum quantities required.

SPOOL SPECIFICATIONS

GRADES	ASTM STANDARDS			
	A615-40	A615-60	A615-80	Future Grade: 100
		A706-60	A706-80	
		A615-60/A706 GR 60	A615-80/A706 GR 80	
	CSA G30.18 STANDARDS			
		400R	500R	Future Grade: 600
		400W	500W	

SIZES	US IMPERIAL BAR SIZES					
	#3	#4	#5	#6	#7	#8
	CANADIAN METRIC BAR SIZES					
	10M	15M	20M	25M		

STANDARD SPOOL WEIGHT IN TONS

2 tons, 3.5 tons, 5 tons, future weight(s) 8 tons